

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

ZyXEL GS1920-24v2, 28 Port Smart Managed Switch 24x Gigabit Copper and 4x Gigabit dual pers., hybrid mode, standalone or NebulaFlex Cloud



Модел : GS1920-24V2-EU0101F

ZyXEL GS1920-24v2, 28 Port Smart Managed Switch 24x Gigabit Copper and 4x Gigabit dual pers., hybrid mode, standalone or NebulaFlex Cloud

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): No

Uplink портове: 4 dual personality

Свободни (10GB) слотове: No

Управление: Web interface; Management through SNMP; Remote firmware upgrade by Web; Configuration saving and retrieving; DHCP; NTP; SNMP v1, v2c, v3; SNMP trap group; RMON (1, 2, 3, 9); ICMP echo/echo reply; Syslog; IEEE 802.1AB LLDP; IEEE 802.1AB LLDP-MED

Stackable: ZyXEL iStacking

Fans: Fanless design

Захранване: Input voltage of AC: 100 - 240 V AC, 50/60 Hz;

Max. power consumption: 22.5 (watt)

Routing: Layer 2 Only

Памет (Flash, RAM): Flash Memory: 32 MB; RAM: 256 MB

Капацитет за маршрутизиране/превключване, Gbps: 56 Gbps

Пропускателна способност, Mpps: 42 Mpps

MAC адреси: 16000 MAC address table size

VLAN (брой, стандарти): 802.1Q Static VLANs/Dynamic VLANs: 1 K/4 K; Port-based VLAN; Protocol-based VLAN; IP Subnet-based VLAN; MAC-based VLAN; Private VLAN; Voice VLAN; VLAN ingress filtering; GVRP; LACP algorithm of source/destination MAC/IP; L2PT

QoS: 8 hardware queues per port; 802.1p queuing methods: SPQ, WRR, WFQ; Storm control: broadcast, multicast, unknown unicast (DLF); 802.1p Class of Service (SPQ, WFQ, SPQ/WFQ combination capable); DiffServ (DSCP); Rate limiting per IP/TCP/UDP per port

L2 мрежови стандарти: IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x flow control, IEEE 802.3az EEE, IEEE 802.3ad LACP aggregation, IEEE 802.1AB, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1X

L3 мрежови стандарти: -

IPv6 functionality: IPv6 over Ethernet, IPv6 addressing

architecture, Dual stack, ICMPv6, Path MTU, Minimum path MTU size of 1280, Encapsulation for maximum PMTU of 1500, Neighbor discovery, DHCPv6 relay, Default DHCP client mode, DAD (Duplicated Address Detection)
Сигурност: 802.1X, Port security, Layer 2 MAC filtering, Layer 3 IP filtering, RADIUS, TACACS+, SSL, MAC freeze, DHCP snooping, ARP inspection, Static IP-MAC-Port binding, Port isolation, IP source guard, ACL packet filtering (IPv4/IPv6), Guest VLAN, CPU protection
Размери (Ш, Д, В), mm: 441 x 131 x 44
Опция за монтаж: Rackmount

Цена : 441.74 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 януари, 2025