


МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

ZyXEL XGS4600-32 L3 Managed Switch, 28 port Gig and 4x 10G SFP+, stackable, dual PSU



Модел : XGS4600-32-ZZ0102F

ZyXEL XGS4600-32 L3 Managed Switch, 28 port Gig and 4x 10G SFP+, stackable, dual PSU

Суич, тип: Fixed Port

Общ брой портове: 32

Основни портове, тип: 24x 100/1000Base-T + 4x Gigabit combo (SFP/RJ-45)

Power Over Ethernet (PoE): -

Uplink портове: 4x 10 GbE SFP+

Свободни (10GB) слотове: -

Управление: Web-based management, Telnet, SSH, SNMP, RS-232c local console, IP management: static IP or DHCP assigned IP, Four RMON groups, Port mirroring, IEEE 802.1AB LLDP, Transceiver DDMI information (including MIB), sFlow

Stackable: Zyxel iStacking, up to 24 switches managed by a single IP address; Physical stacking up to 4 switches

Fans: Fanless

Захранване: External Power supply: 100 to 240V AC, 50/60 Hz, Max. power consumption: 47W

Routing: Static routing, IPv6 static routing, Equal Cost Multipath Routing (ECMP), Virtual Router Redundancy Protocol (VRRP), Routing table: 12K

Памет (Flash, RAM): Packet buffer: 4 MB; Flash/RAM: 64 MB/1 GB

Капацитет за маршрутизиране/превключване, Gbps: 136 Gbps

Пропускателна способност, Mpps: 101.1 Mpps

MAC адреси: 32 K; Max. 8K IPv4 entries; Max. 4K IPv6 entries

VLAN (брой, стандарти): Up to 4 K static/dynamic VLANs, IEEE 802.1Q tag-based and portbased VLAN, Guest VLAN, GVRP automatic VLAN member registration, IP classification VLAN, VLAN counter, VLAN search, VLAN translation, VLAN MAC limit

QoS: IEEE 802.1p with 8 priority queues per port, WFR, WRR, SPQ scheduling algorithms, DSCP/DSCP to 802.1p priority mapping, IGMP/IGMP snooping, Multicast VLAN Registration (MVR), Congestion control on all ports, Selective Q-in-Q
L2 мрежови стандарти: IEEE 802.3, 802.3u, 802.3ab, 802.3z, 802.3x, 802.3az, 802.1p CoS, 802.1D, 802.1w, 802.1s, 802.1q, 802.1x, 802.3ad

IPv6 functionality: IPv6 over Ethernet, IPv6 addressing, ICMPv6, Dual Stack, IPv6 static routing, Neighbor discovery, DHCPv6 relay

Сигурност: Port security, IP filtering, TCP/UDP socket filtering, IEEE 802.1X port-based authentication, TACACS+, Two-level security by specific SNMP read/write community, Multiple access permission, SSH, SSL/TLS, IP source guard, Loop guard

Размери (Ш, Д, В), mm: 441 x 270 x 44

Опция за монтаж: Rack mounting

Цена : 4659.64 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 14 август, 2025