

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Суич ZYXEL XS1930-10, 8 портов управляем, 10Gb, 2xSFP, за монтаж в шкаф



Модел : ZYXEL-XS1930-10

Суич ZYXEL XS1930-10, 8 портов управляем, 10Gb, 2xSFP, за монтаж в шкаф

Суич, тип Fixed Port

Общ брой портове 10

Основни портове, тип 10x10GBase-T

Uplink портове 2 dual personality

Управление Web interface; Management through SNMP;
Remote firmware upgrade by Web; Configuration saving and retrieving; DHCP; NTP; SNMP v1, v2c, v3; SNMP trap group; RMON (1, 2, 3, 9); ICMP echo/echo reply; Syslog; IEEE 802.1AB LLDP; IEEE 802.1AB LLDP-MED

Stackable ZyXEL iStacking™

Fans Fanless design

Захранване Input voltage: 100 - 240 V AC, 50/60 Hz; Max.

power consumption: 94.1 (watt)

Routing Layer 2 Only

Памет (Flash, RAM) -

Капацитет за маршрутизиране/превключване, Gbps 240 Gbps

Пропускателна способност, Mpps 178.6 Mpps

MAC адреси 16000 MAC address table size

VLAN (брой, стандарти) 802.1Q Static VLANs/Dynamic

VLANs: 1 K/4 K; Port-based VLAN; Protocol-based VLAN; IP Subnet-based VLAN; MAC-based VLAN; Private VLAN; Voice VLAN; VLAN ingress filtering; GVRP; LACP algorithm of source/destination MAC/IP; L2PT

QoS 8 hardware queues per port; 802.1p queuing methods: SPQ, WRR, WFQ; Storm control: broadcast, multicast, unknown unicast (DLF); 802.1p Class of Service (SPQ, WFQ, SPQ/WFQ combination capable); DiffServ (DSCP); Rate limiting per IP/TCP/UDP per port

L2 мрежови стандарти IEEE 802.3ab, IEEE 802.3an, IEEE 802.3ae, IEEE 802.3z, IEEE 802.3x flow control, IEEE 802.3az IEEE support, IEEE 802.3ad LACP aggregation, IEEE 802.1AB, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1X

L3 мрежови стандарти - IPv6 functionality IPv6 over Ethernet, IPv6 addressing architecture, Dual stack, ICMPv6, Path MTU, Minimum path MTU size of 1280, Encapsulation for maximum PMTU of 1500, Neighbor discovery, DHCPv6 relay



Сигурност 802.1X, Port security, Layer 2 MAC filtering,
Layer 3 IP filtering, RADIUS, TACACS+, SSL, MAC freeze,
DHCP snooping, ARP inspection, Static IP-MAC-Port binding,
Port isolation, IP source guard, ACL packet filtering
(IPv4/IPv6), CPU protection
Размери, mm 440 x 330 x 44.5 mm, 19" rackmount
Гаранция: 60

Цена : 1147.33 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 03 февруари, 2025