

КОМПЮТРИ И СЪРВЪРИ > Сервъри

Dell PowerEdge R7515 Server, AMD EPYC 7302P 3GHz, 16C/32T, 128MB L3 Cache, 155W, 3.5" Chassis with up to 8 Drives, 16GB RDIMM 3200MT/s, iDRAC9 Enterprise 15G, 2x 480GB SSD S3 Read Intensive 3.5in HYB CARR, PERC H330, Dual PSU 750W, 6 Fans, 36M NBD



Модел : 486-46772

Dell PowerEdge R7515 Server, AMD EPYC 7302P 3GHz, 16C/32T, 128MB L3 Cache, 155W, 3.5" Chassis with up to 8 Drives, 16GB RDIMM 3200MT/s, iDRAC9 Enterprise 15G, 2x 480GB SSD S3 Read Intensive 3.5in HYB CARR, PERC H330, Dual PSU 750W, 6 Fans, 36M NBD

Серия: PowerEdge R7515

Процесор: AMD EPYC 7302P 3GHz, 16C/32T, 128MB L3 Cache, 155W

Памет, GB: 16GB RDIMM, 3200MT/s, Dual Rank

Памет, слотове: 16 DDR4 RDIMM/LRDIMM slots, Type: RDIMM/LDIMM, Up to 3200MT/s, Max. RAM: RDIMM - 1TB, LRDIMM - 2TB

Твърд диск, GB: 2x 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 3.5in HYB CARR, 1 DWPD

Дисков контролер: PERC H330 RAID Controller, Minicard

Брой поддържани дискове: 8xLFF (3.5" Chassis with up to 8 Drives)

Оптично устройство: -

Мрежа: 2x 1GbE, 2x 10GbE BT, 2x 10GbE SFP+, 2x 25GbE SFP28

Разширителен слот: No PCIe Riser; Up to 4: 2x Gen3 slots (1 x8; 1 x16), 2x Gen4 slots (2 x16)

Интерфейс: Front: 1x Dedicated iDRAC direct micro-USB, 2x USB 2.0, 1x Video; Rear: 2x 1GbE, 1x Dedicated iDRAC network port, 1x Serial, 2x USB 3.0, 1x Video

Порт за отдалечено управление: yes

Захранване: Dual, Hot-plug, Redundant Power Supply (1+1), 750W

Съвместими операционни системи: Canonical Ubuntu Server LTS, Citrix HypervisorTM, Microsoft Windows Server with Hyper-V, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi

Софтуер за управление: iDRAC9 Enterprise 15G

Форм-фактор: 2U Rack

Тип на шасито: Hot-Plug

Други: 6 Fans

Цена : 8455.21 лв. с ДДС



Наличност: Този продукт е бил добавен в нашия каталог на Ср 21 май, 2025