

КОМПЮТРИ И СЪРВЪРИ > Сървъри

Dell PowerEdge R250, Chassis 4 x 3.5 HotPlug, Xeon E-2314, 16GB, 1x480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, Rails, Bezel, Broadcom 5720, PERC H355, iDRAC9 Express 15G, 450W, 3Y Basic Onsite



Модел : PER2505A

Dell PowerEdge R250, Chassis 4 x 3.5 HotPlug, Xeon E-2314, 16GB, 1x480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, Rails, Bezel, Broadcom 5720, PERC H355, iDRAC9 Express 15G, 450W, 3Y Basic Onsite

Серия: PowerEdge R250

Процесор: Intel Xeon E-2314 2.8GHz, 8M Cache, 4C/4T, Turbo (65W), 3200 MT/s

Памет, GB: 16 GB

Памет, слотове: 4x DDR4 DIMM slots, supports UDIMM 128 GB max, speeds up to 3200 MT/s; Supports unregistered ECC DDR4 DIMMs only Note: For Pentium processor, the maximum memory speed is 2666 MT/s.

Твърд диск, GB: 1x 480GB SSD SATA Mix Use 6Gbps 512 2.5in Hot-plug AG Drive, 3.5"; HYB CARR

Дисков контролер: PERC H355

Брой поддържани дискове: Up to 4x 3.5" hot swap SAS/SATA (HDD/SSD) max 30.72 TB

Оптично устройство: -

Мрежа: Broadcom 5720, Onboard LOM 1GbE x2

Разширителен слот: 2 PCIe slots: 1 x8 Gen4 (x16 connector) low profile, half length, 1 x8 Gen4 (x8 connector) low profile, half length

Интерфейс: Front: 1x USB 2.0, 1x iDRAC Direct (Micro-AB USB) port; Rear: 1x USB 2.0, 1x iDRAC ethernet port, 1x USB 3.0, 1x VGA, 1x Serial port; Internal: 1x USB 3.0 (optional)

Порт за отдалечено управление: yes

Захранване: 450W

Съвместими операционни системи: Canonical Ubuntu Server LTS, Citrix Hypervisor, Microsoft Windows Server with Hyper-V, Red Hat Enterprise Linux, SUSE Linux Enterprise Servers, VMware ESXi

Софтуер за управление: iDRAC9 Express 15G

Форм-фактор: 1U Rack

Тип на шасито: Hot-Plug

Други: Rails, Bezel

Цена : 4113.97 лв. с ДДС



Наличност: Този продукт е бил добавен в нашия каталог на Пн 09 юни, 2025