

МРЕЖОВА ТЕХНИКА > СВИЧОВЕ

D-Link 24-port Gigabit Managed Switch plus 4 Combo 1000BaseT/SFP



Модел : DGS-2000-28

D-Link 24-port Gigabit Managed Switch plus 4 Combo 1000BaseT/SFP

Свич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x 10/100/1000BASE-T ports

Power Over Ethernet (PoE): -

Uplink портове: 4x 100/1000 Mbps GbE/SFP combo ports

Свободни (10GB) слотове: -

Управление: Web-based GUI (IPv4/IPv6); Command Line Interface (CLI) through Telnet or SSH; Telnet Server/Client (Support IPv4/IPv6); Command logging; SNMP; System log; RMON; LLDP; BootP/DHCP client; DHCP; SNTP

Stackable: -

Fans: Fanless

Захранване: Internal universal power supply: AC Input: 100 to 240 V AC, 50/60 Hz; Max. Power Consumption: 17.32 W

Routing: Static

Памет (Flash, RAM): CPU Memory: 256 MB DDR3; packet

Buffer: 4.1 Mbits; Flash Memory: 32 MB

Капацитет за маршрутизиране/превключване, Gbps: 56 Gbps

Пропускателна способност, Mpps: 77.4 Mpps

MAC адреси: 8K entries; Up to 256 static MAC entries

VLAN (брой, стандарти): 802.1Q tagged VLAN; VLAN groups: Max. 256; Port-based VLAN, Asymmetric VLAN, Port-based Q-in-Q, ISM VLAN (multicast VLAN), Voice VLAN, Auto surveillance VLAN, VLAN Translation

QoS: CoS based on: Switch port, DSCP; Bandwidth control - Port-based (ingress, egress, min. granularity 16 Kbps);

Queue handling: Strict priority (SPQ), Weighted Round Robin (WRR); 8 outbound queues

L2 мрежови стандарти: IEEE 802.3 10BASE-T Ethernet, IEEE 802.3u 100BASE-TX Fast Ethernet, IEEE 802.3ab 1000BASE-T Gigabit Ethernet, Auto-negotiation, IEEE 802.3x Flow Control, IEEE 802.3z 1000BASE-X Gigabit Fiber

L3 мрежови стандарти: RFC768 UDP; RFC791 IP; RFC792 ICMPv4; RFC2463, 4443 ICMPv6; RFC793 TCP; RFC826 ARP; RFC1321, 2284, 2865, 2716, 3580 Extensible Authentication Protocol (EAP)

IPv6 functionality: Max. 4 IPv4/IPv6 interfaces; Max. 128 IPv6 entries; IPv6 Neighbor Discovery (ND) - 256 Entries; IPv6 Inspection - Max. 63 entries; RFC2460 IPv6

Сигурност: Port security (Up to 64 MAC addresses per port);
Smart IP-MAC-Port Binding; Broadcast/Multicast/Unicast
storm control; IP inspection; Duplicate Address Detection
(DAD); D-Link Safeguard Engine; DoS attack prevention;
Traffic segmentation; SSH
Размери (Ш, Д, В), mm: 440 x 140 x 44 mm
Опция за монтаж: Rackmount (1U)
Други: Auto MDI/MDIX adjustment for all twisted-pair ports

Цена : 552.64 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 18 септември, 2025