

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

## D-Link 24-port PoE Gigabit Managed Switch + 4 Combo 1000BaseT/SFP



Модел : DGS-2000-28P

D-Link 24-port PoE Gigabit Managed Switch + 4 Combo 1000BaseT/SFP

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): IEEE 802.3af, IEEE 802.3at,  
Maximum PoE Budget: 193W, Ports 1 to 24 compliant with  
IEEE 802.3at

Uplink портове: 4 dual personality

Свободни (10GB) слотове: No

Управление: Web-based GUI (IPv4/IPv6), CLI through Telnet  
or SSH, Telnet Server/Client (Support IPv4/IPv6), Command  
logging, SNMP, System log, RMON v1, LLDP, BootP/DHCP  
client, DHCP, SNTp

Stackable: No

Fans: 2 x Smart fan

Захранване: Internal universal power supply: AC Input: 100  
to 240 V AC, 50/60 Hz; Max. Power Consumption: 236.9 W  
(PoE on), 30.6 W (PoE off)

Routing: Layer 3 Lite

Памет (Flash, RAM): CPU Memory: 256 MB DDR3, Flash  
Memory: 32 MB

Капацитет за маршрутизиране/превключване, Gbps: 56  
Gbps

Пропускателна способност, Mpps: 41.7 Mpps

MAC адреси: 8000 MAC address table size

VLAN (брой, стандарти): 802.1Q tagged VLAN; VLAN  
groups: Max. 256; Port-based/Asymmetric/Voice/Auto  
surveillance VLAN; Port-based Q-in-Q; ISM VLAN (multicast  
VLAN); VLAN Translation

QoS: CoS based on: Switch port, DSCP, Bandwidth control -  
Port-based (ingress, egress, min. granularity 16 Kbps);  
Queue handling: Strict priority (SPQ), Weighted Round Robin  
(WRR); 8 outbound queues

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE  
802.3ab, IEEE 802.3x, IEEE 802.3z, IEEE 802.1D, IEEE  
802.1w, IEEE 802.1s, IEEE 802.3ad, IEEE 802.1Q, IEEE  
802.1p, IEEE 802.1X, IEEE 802.3ah, IEEE 802.3af, IEEE  
802.3at

L3 мрежови стандарти: Default Routing, Static Route: Max.  
128 IPv4 entries, Max. 128 IPv6 entries

IPv6 functionality: RFC1981 Path MTU Discovery, RFC2460

IPv6, RFC2461, 4861 Neighbor Discovery, RFC2462, 4862  
IPv6 Stateless Address Auto-configuration, RFC2893, 4213  
IPv4/IPv6 dual stack function  
Сигурност: Port security (Up to 64 MAC addresses per port);  
Smart IP-MAC-Port Binding; Broadcast/Multicast/Unicast  
storm control; IP inspection; DAD; D-Link Safeguard Engine;  
DoS attack prevention; Traffic segmentation; SSH  
Размери (Ш, Д, В), mm: 440 x 250 x 44 mm  
Опция за монтаж: Rackmount (1U)

Цена : 1291.08 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 27 ноември, 2025