

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

ZyXEL XGS2220-30HP, L3 Access Switch, 400W PoE, 16xPoE+/10xPoE++, 24x1G RJ45 2x10mG RJ45, 4x10G SFP+ Uplink, incl. 1 yr NebulaFlex Pro



Модел : XGS2220-30HP-EU0101F

ZyXEL XGS2220-30HP, L3 Access Switch, 400W PoE, 16xPoE+/10xPoE++, 24x1G RJ45 2x10mG RJ45, 4x10G SFP+ Uplink, incl. 1 yr NebulaFlex Pro

Суич, тип: Fixed Port, Layer 3 Access

Общ брой портове: 30

Основни портове, тип: 24x1G RJ45 (100/1000 Mbps) +

2x10mG RJ45 (100M/1G/2.5G/5G/10G Ethernet)

Power Over Ethernet (PoE): 26 PoE ports: 16x Gigabit RJ-45 PoE+ ports + 8x Gigabit RJ-45 PoE++ (60 W) ports + 2x 10G Multi-Gigabit (1G/2.5G/5G/10G) RJ-45 PoE++ (60 W) ports

Uplink портове: 4xSFP+

Свободни (10GB) слотове: -

Управление: Standalone management by Web interface; Cloud management by Nebula Control Center; Management through Console, Telnet, SNMP; Multilevel CLI; DHCP

Stackable: Physical stacking (In the future firmware release)

Fans: 1 x smart fan

Захранване: 100 - 240 V AC, 50/60 Hz; Max. power consumption: 37.62W

Routing: Static; Static route: 64

Памет (Flash, RAM): 64 MB/1 GB (Flash/RAM)

Капацитет за маршрутизиране/превключване, Gbps: 168 Gbps

Пропускателна способност, Mpps: 125 Mpps

MAC адреси: 32 K

VLAN (брой, стандарти): 802.1Q static VLANs/dynamic

VLANs: 4 K/4 K; VLAN isolation; Port-based/Vendor ID based/Protocol-based/IP

subnet-based/MAC-based/Private/Voice VLAN; Independent VLAN Learning (IVL); VLAN Translation/trunking/mapping; QinQ; GVRP; L2PT

QoS: No. of hardware queues per port

(Standalone/stacking): 8*/6; Storm control and event log; Port-based rate limiting; Rate limiting per IP/TCP/UDP per port; Policy-based rate limiting; 802.3x flow control; 802.1p Class of Service; DSCP

L2 мрежови стандарти: IEEE 802.3z, IEEE 802.3ab, IEEE 802.3an, IEEE 802.3ae, IEEE 802.1X

L3 мрежови стандарти: IEEE 802.1D Spanning Tree Protocol (STP); IEEE 802.1w Rapid Spanning Tree Protocol

(RSTP); IEEE 802.1s Multiple Spanning Tree Protocol (MSTP);
IEEE 802.3ad LACP

IPv6 functionality: Max. 1 K IPv4 entries; Max. 512 IPv6
entries; IP source guard (IPv4*/IPv6); ACL packet filtering
(IPv4/IPv6); Syslog (IPv4/IPv6); IPv6 over Ethernet (RFC
2464); IPv6 addressing architecture (RFC 4291); IPv6
binding- static/dynamic

Сигурност: Port security; Layer 2 MAC filtering; Layer 3 IP
filtering; Layer 4 TCP/UDP socket filtering; Static MAC
forwarding; RADIUS; TACACS+; SSH v2; SSL; DHCP;

Размери (Ш, Д, В), mm: 441 x 330 x 44 mm

Опция за монтаж: Rackmount

Други: Rack mounting kit included

Цена : 2191.36 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 18 декември, 2025