

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Декодери

HikVision Network recorder, 4 IP Cameras, up to 8 MP (4x1080p/1x4K), H.265+, 1 SATA HDD up to 10TB, 2 USB, 100Mbit; Video input: HDMI 4K, VGA 1080p



Модел : DS-7604NXI-K1

HikVision Network recorder, 4 IP Cameras, up to 8 MP (4x1080p/1x4K), H.265+, 1 SATA HDD up to 10TB, 2 USB, 100Mbit; Video input: HDMI 4K, VGA 1080p

Тип: IP Recorder

Брой канали: 4 (IP Video Input)

HDMI: 1-ch, 4K (3840 x 2160)/30 Hz, 2K (2560 x 1440)/60 Hz, 1920 x 1080/60 Hz, 1600 x 1200/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz

VGA: 1-ch, 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz

Видео изходен режим: HDMI/VGA simultaneous output

Капацитет: Incoming: 40 Mbps, Outgoing: 80 Mbps

Аудио: 1-ch, RCA (Linear, 1 kOhm); Two-Way Audio: 1-ch, RCA (2.0 Vp-p, 1 kOhm, using the audio input)

Видео компресия: H.265/H.265+/H.264+/H.264

Аудио компресия: G.711ulaw/G.711alaw/G.722/G.726/AAC

Резолюция на запис: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Дистанционна връзка: 128

Мрежови протоколи: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS

Мрежов интерфейс: 1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface

Спомагателен интерфейс: 1x SATA interface (Up to 10 TB capacity for each HDD), Front panel: 1 Ч USB 2.0; Rear panel: 1 Ч USB 2.0

Захранване: 12 VDC, 1.5 A, Consumption: <= 10 W (without HDD)

Power Over Ethernet (PoE): -

Размери (Ш, Д, В), mm: 320 mm x 240 mm x 48 mm

Тегло, g: <= 1 kg

Други: AI By Device Facial recognition, perimeter protection, motion detection 2.0; AI By Camera Facial recognition, perimeter protection, throwing objects from building, motion detection 2.0, ANPR, VCA; Motion Detection 2.0; Perimeter Protection

Цена : 288.67 лв. с ДДС



Наличност: Този продукт е бил добавен в нашия каталог на Пт 24 октомври, 2025