

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

GB B760 A ELITE AX DDR4



Модел : GB B760 AORUS ELITE AX DDR4

GB B760 A ELITE AX DDR4

CPU's supported: LGA1700 socket: Support for the 14th, 13th, and 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors*; L3 cache varies with CPU

Memory type: Support for DDR4 5333(O.C.) / 5133(O.C.) / 5000(O.C.) / 4933(O.C.) / 4800(O.C.) / 4700(O.C.) / 4600(O.C.) / 4500(O.C.) / 4400(O.C.) / 4300(O.C.) / 4266(O.C.) / 4133(O.C.) / 4000(O.C.) / 3866(O.C.) / 3800(O.C.) / 3733(O.C.) / 3666(O.C.) / 3600(O.C.) / 3466(O.C.) / 3400(O.C.) / 3333(O.C.) / 3300(O.C.) / 3200 / 3000 / 2933 / 2666 / 2400 / 2133 MT/s memory modules; 4 x DDR DIMM sockets supporting up to 128 GB (32 GB single DIMM capacity) of system memory; Dual channel memory architecture; Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode); Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules; Support for Extreme Memory Profile (XMP) memory modules

Chipset: Intel® B760 Express Chipset

Graphics: Integrated Graphics Processor-Intel® HD Graphics support: 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz; * Support for HDMI 2.0 version and HDCP 2.3.; 1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz; * Support for DisplayPort 1.2 version and HDCP 2.3

Expansion Slots: CPU: 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x16 (PCIEX16); * For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot.; Chipset: 2 x PCI Express x16 slots, supporting PCIe 3.0 and running at x1 (PCIEX1_1, PCIEX1_2)

Storage: CPU: 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2A_CPU); Chipset: 2 x M.2 connectors (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB, M2M_SB); 4 x SATA 6Gb/s connectors; RAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices

I/O: 1 x USB Type-C® port, with USB 3.2 Gen 2 support; 1 x USB 3.2 Gen 2 Type-A port (red); 4 x USB 3.2 Gen 1 ports; 4 x USB 2.0/1.1 ports; 2 x SMA antenna connectors (2T2R); 1 x HDMI port; 1 x DisplayPort; 1 x RJ-45 port; 1 x

optical S/PDIF Out connector; 2 x audio jacks
Connectors: 1 x 24-pin ATX main power connector; 1 x 8-pin ATX 12V power connector; 1 x 4-pin ATX 12V power connector; 1 x CPU fan header; 1 x CPU fan/water cooling pump header; 3 x system fan headers; 1 x system fan/water cooling pump header; 2 x addressable LED strip headers; 2 x RGB LED strip headers; 3 x M.2 Socket 3 connectors; 4 x SATA 6Gb/s connectors; 1 x front panel header; 1 x front panel audio header; 1 x USB Type-C® header, with USB 3.2 Gen 2 support; 1 x USB 3.2 Gen 1 header; 2 x USB 2.0/1.1 headers; 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only); 1 x reset button; 1 x Q-Flash Plus button; 1 x reset jumper; 1 x Clear CMOS jumper
Audio: Realtek®; Audio CODEC; High Definition Audio; 2/4/5.1/7.1-channel
LAN: Realtek®; 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
BIOS: 1 x 256 Mbit flash; Use of licensed AMI UEFI BIOS; PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Form Factor: ATX Form Factor; 30.5cm x 24.4cm
OS: Support for Windows 11 64-bit; Support for Windows 10 64-bit
Other: Intel®; Wi-Fi 6E AX211 (For PCB rev. 1.0); WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands; BLUETOOTH 5.3; Support for 11ax 160MHz wireless standard and up to 2.4 Gbps data rate; Realtek®; Wi-Fi 6E RTL8852CE (For PCB rev. 1.1); WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands; BLUETOOTH 5.3; Support for 11ax 160MHz wireless standard and up to 2.4 Gbps data rate
Warranty: 36 Months

Цена : 376.37 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Вт 12 август, 2025