

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Aruba Instant On 1930 24G Class 4 PoE 4SFP/SFP+ 370W Switch



Модел : JL684B

Aruba Instant On 1930 24G Class 4 PoE 4SFP/SFP+ 370W Switch

Суич, тип: Fixed Port, Smart Managed

Общ брой портове: 28

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T; PoE power: 370 W, Class 4

Uplink портове: 4 SFP/SFP+

Свободни (10GB) слотове: No

Управление: Aruba Instant On Portal; Web browser; SNMP Manager; Management VLAN ID

Stackable: No

Fans: Variable speed fans

Захранване: AC voltage: 100 - 127/200 - 240 VAC;

Maximum power rating: 439 W, Current: 4.8/2.4 A;

Frequency: 50/60 Hz

Routing: Layer 3 IPv4 static routing (Supports manual routing configuration of up to 32 static routes)

Памет (Flash, RAM): 512 MB SDRAM, 256 MB flash; packet buffer: 1.5 MB

Капацитет за маршрутизиране/превключване, Gbps: 128 Gbps

Пропускателна способност, Mpps: 95.23 Mpps

MAC адреси: 16000 MAC address table size

VLAN (брой, стандарти): IEEE 802.1p/Q VLAN tagging; IEEE 802.1Q VLAN support - Support for up to 256 VLANs with a VLAN ID range of 2-4093; RADIUS assigned VLAN, dynamic VLAN creation, guest VLAN or into an unauthenticated VLAN; Auto-voice VLAN.

QoS: Traffic prioritization - time-sensitive packets (like VoIP and video) with priority over other traffic based on DSCP or IEEE 802.1p classification. IEEE 802.1p/DSCP priority to queue mapping. Supports SP or WRR. Advanced classifier based QoS.

L2 мрежови стандарти: 802.3 10BASE-T, 802.3u 100BASE-TX, 802.3ab 1000BASE-T, 802.3z 1000BASE-X, 802.2af/at PoE, 802.3x, 802.1Q VLANs, 802.1p Priority, 802.3ad LACP, 802.1X, 802.3az

L3 мрежови стандарти: 802.1D (Spanning Tree Protocol), 802.1W: Rapid Spanning Tree Protocol, 802.1S: Multiple Spanning Tree Protocol; 802.1AB Link Layer Discovery

Protocol

IPv6 functionality: IPv6 Host mode - Enables switches to be managed and deployed at the IPv6 network's edge

Сигурност: TPM, IEEE 802.1Q VLAN support; IEEE 802.1X access control; Automatic denial-of-service protection;

Packet storm protection; RADIUS; RADIUS accounting;

Management VLAN ID; Link Flap prevention

Размери (Ш, Д, В), mm: 442.5 x 264.7 x 44

Опция за монтаж: Rackmount (1U)

Цена : 1158.60 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 29 август, 2025