

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision 2 MP AcuSense Fixed Bullet Network Camera with Strobe Light and Audible Warning, 4 mm, IR up to 60m, 120 dB WDR, 3D DNR, H.265+, IP67, Built-in microphone and speaker, Built-in memory card slot up to 256 GB, 12Vdc/PoE 12W



Модел : DS-2CD2T26G2-ISU/SL(D)

HikVision 2 MP AcuSense Fixed Bullet Network Camera with Strobe Light and Audible Warning, 4 mm, IR up to 60m, 120 dB WDR, 3D DNR, H.265+, IP67, Built-in microphone and speaker, Built-in memory card slot up to 256 GB, 12Vdc/PoE 12W

Тип: IP

Сензор, тип: CMOS

Размер на оптичния сензор: 1/2.8" Progressive Scan CMOS

Резолюция, MP: 2 MP

Фокално разстояние: 4 mm, horizontal FOV: 86°, vertical FOV: 47°, diagonal FOV: 102°

Минимална осветеност, lx: 0.002 Lux @ (F1.4, AGC ON), B/W: 0 Lux with IR

IR осветление: IR up to 60m

Максимална резолюция, pixels: 1920x1080

Формати на компресиране: Main stream:

H.265+/H.265/H.264+/H.264; Sub-stream:

H.265/H.264/MJPEG

Скорост на предаване на кадри: Main Stream - 50 Hz: 25 fps (1920x1080, 1280x720), 60 Hz: 30 fps (1920x1080, 1280x720); Sub-Stream - 50 Hz: 25 fps (640x480, 640x360), 60 Hz: 30 fps (640x480, 640x360)

Поддържани мрежови протоколи: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets

Мрежов интерфейс: 1 RJ45 10M/100M self-adaptive Ethernet port

Безжична мрежа: -

Power Over Ethernet (PoE): PoE: 802.3af, Class 3, 36 V to 57 V, 0.34 A to 0.21 A, max. 12 W

Входни/Изходни портове: Alarm: 1 input, 1 output; Audio: 1 input (line in), 1 output (line out)

Звук: Built-in microphone and speaker

Захранване: 12 VDC, 0.88 A, max. 10.6 W

Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 256 GB

Нощно виждане: IR cut filter

Външен монтаж: yes

Влагозащита: IP67

Вандалоустойчивост: -

Работна температура: -30 °C to 60 °C

Диапазон на влажността при експлоатация: Humidity
95% or less (non-condensing)

Сигурност: Password protection, complicated password,
HTTPS encryption, 802.1X authentication (EAP-TLS,
EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and
digest authentication for HTTP/HTTPS, WSSE and digest
authentication for Open Network Video Interface

Размери (Ш, Д, В), mm: 289 x 93.1 x 91.2 mm

Цена : 521.02 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 24 септември, 2025