

КОМПЮТРИ И СЪРВЪРИ > Сървъри

Dell PowerEdge R260, 2.5" up to 6 Hot Plug, Intel Xeon E-2414, 1x16GB DDR5 UDIMM, 1x480GB SSD SATA RI 6Gbps 512 2.5" HP AG Drive, 1 DWPD, 1U, 2U 2, 4-Post Static Rails, Bezel, Broadcom 5720 Dual Port 1Gb LOM, PERC H355, iDRAC9 Basic, 3Y Basic Onsite



Модел : EMEA_PER260SPL2

Dell PowerEdge R260, 2.5" up to 6 Hot Plug, Intel Xeon E-2414, 1x16GB DDR5 UDIMM, 1x480GB SSD SATA RI 6Gbps 512 2.5" HP AG Drive, 1 DWPD, 1U, 2U 2, 4-Post Static Rails, Bezel, Broadcom 5720 Dual Port 1Gb LOM, PERC H355, iDRAC9 Basic, 3Y Basic Onsite

Серия: PowerEdge R260

Процесор: Intel Xeon E-2414 2.6G, 4C/4T, 8M Cache, Turbo, HT (55W) DDR5-4800

Памет, GB: 1x16GB DDR5 UDIMM

Памет, слотове: 4 DDR5 DIMM slots, ECC UDIMM, Up to 4400 MT/s, Max. RAM: ECC UDIMM 128 GB

Твърд диск, GB: 1x480GB SSD SATA RI 6Gbps 512 2.5" HP AG Drive

Дисков контролер: PERC H355

Брой поддържани дискове: Up to 6 x 2.5-inch hot-plug SAS/SATA HDD/SSD, max 46.08TB

Оптично устройство: 1 DWPD

Мрежа: Broadcom 5720 Dual Port 1Gb LOM

Разширителен слот: Slot 1: 1 x8 slot with x8 bandwidth, Half Length, Low Profile; Slot 2: 1 x16 slot with x8 bandwidth, Half Length, Low Profile

Интерфейс: 2 x 1GbE LOM; Front: 1x iDRAC Direct (Micro-AB USB), 1x USB 2.0; Rear: 1x Dedicated iDRAC Ethernet port, 1x USB 2.0, 1x USB 3.2 Gen1, 1x VGA, 1x Serial; Internal: 1x USB 3.2 Gen1

Порт за отдалечено управление: yes

Захранване: 700 W Titanium 200 — 240 VAC or 240 VDC, non redundant

Съвместими операционни системи: Canonical Ubuntu Server LTS, Microsoft Windows Server with Hyper-V, RedHat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi

Софтуер за управление: iDRAC9 Basic 16G

Форм-фактор: 1U Rack

Тип на шасито: Hot-Plug

Други: 4-Post Static Rails, Bezel; Up to five Standard (STD) fans and one optional High Performance (HPR) fan



Цена : 5090.62 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 18 декември, 2025