

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Cisco Catalyst 9300 48-port (12 mGig, 36 2.5Gbps), UPOE, Network Essentials



Модел : C9300-48UXM-E

Cisco Catalyst 9300 48-port (12 mGig, 36 2.5Gbps), UPOE, Network Essentials

Суич, тип: Modular

Общ брой портове: 48

Основни портове, тип: 36x 100M/1G/2.5G + 12x

Multigigabit (10G/5G/2.5G/1G/100M) ENERGY STAR certified

Power Over Ethernet (PoE): UPOE (60W per port) & IEEE 802.3bt type3 on all ports (24-port switch) or up to 30 ports (48-port switch)

Uplink портове: Modular Uplinks

Свободни (10GB) слотове: -

Управление: Cloud management and monitoring; WebUI

Stackable: Designed for stacking switches as a single virtual switch, enabling customers to have a single management plane and control plane for up to 448 access ports.

Fans: Three field-replaceable fans and support (N+1) redundancy.

Захранване: Redundant; Default AC power supply: 1100W AC

Routing: High-Performance IP routing; Total routed ports: 448

Памет (Flash, RAM): DRAM: 8 GB; Flash: 16 GB; Packet buffer per SKU: 16 MB buffer for 24-or 48-port Gigabit Ethernet models

Капацитет за маршрутизиране/превключване, Gbps: 580 Gbps, Switching capacity with stacking: 1060 Gbps

Пропускателна способност, Mpps: 431.54 Mpps; Forwarding rate with stacking: 788.69 Mpps

MAC адреси: 32 000

VLAN (брой, стандарти): VLAN IDs: 4094; IEEE 802.1Q VLAN

QoS: QoS scale entries: 5 120; Superior QoS (802.1p Class of Service (CoS), DSCP, SRR, CIR)

L2 мрежови стандарти: IEEE 802.3 ab/z/bz/an/x

L3 мрежови стандарти: IEEE 802.1D, RMON I and II standards, SNMPv1, v2c, and v3

IPv6 functionality: IPv6 routing entries: 16 000

Сигурност: ETA, SUDI, AES-256 MACsec encryption, IPsec encryption, Trustworthy solutions built with Cisco Trust Anchor Technologies; Cloud Security: Umbrella DNS



Integration, ASAc

Размери (Ш, Д, В), mm: 485 x 445 x 44 mm

Опция за монтаж: Rackmount

Други: Network Essentials

Цена : 18802.63 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 06 март, 2025