

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

ASUS ROG STRIX X870-E GAM WIF

Модел : ASUS ROG STRIX X870E-E GAM WIF

ASUS ROG STRIX X870-E GAM WIF

USB: Rear USB (Total 13 ports); 2 x USB4® (40Gbps) ports (2 x USB Type-C®); 1 x USB 20Gbps port (1 x USB Type-C® with up to 30W PD Fast-charge)**; 10 x USB 10Gbps ports (9 x Type-A + 1 x USB Type-C®); Front USB (Total 11 ports); 1 x USB 20Gbps connector (supports USB Type-C®); 2 x USB 5Gbps headers support additional 4 USB 5Gbps ports; 3 x USB 2.0 headers support additional 6 USB 2.0 ports; * USB Type-C® power delivery output: 5V/3A; ** USB Type-C® power delivery output: 5V/9V max. 3A, 12V max 2.5A, 15V max. 2.0A

Manufacturer: ASUS

Wireless: Wi-Fi 7; 2x2 Wi-Fi 7 (802.11be); Supports 2.4/5/6GHz frequency band; Support Wi-Fi 7 320MHz bandwidth, up to 6.5Gbps transfer rate.; Bluetooth® v5.4

Memory type: 4 x DIMM slots, max. 256GB, DDR5; Supports up to; 8000+MT/s(OC) with Ryzen™ 9000 Series

Processors; 8400+MT/s(OC) with Ryzen™ 8000 Series

Processors; 8000+MT/s(OC) with Ryzen™ 7000 Series

Processors; ECC and Non-ECC Un-buffered DIMM*; Dual Channel Memory Architecture; Supports AMD EXTended Profiles for Overclocking (EXPO™); NitroPath DRAM Technology; ASUS Enhanced Memory Profile (AEMP)

Features: Extreme Engine Digi+; - 5K Black Metallic Capacitors; ASUS Q-Design; - M.2 Q-Latch; - M.2 Q-Release; - M.2 Q-Slide; - PCIe Slot Q-Release Slim (with PCIe SafeSlot); - Q-Antenna; - Q-Code; - Q-Dashboard; - Q-DIMM; - Q-LED (CPU [red], DRAM [yellow], VGA [white], Boot Device [yellow green]); - Q-Slot; ASUS Thermal Solution; - M.2 heatsinks; - M.2 heatsink backplate; - VRM heatsink design; ASUS EZ DIY; - BIOS FlashBack™ button; - BIOS FlashBack™ LED; - Clear CMOS button; - ProCool II; - Pre-mounted I/O shield; - SafeSlot; - SafeDIMM; Aura Sync; - Addressable Gen 2 headers

CPU's supported: AMD Socket AM5 for AMD Ryzen™ 9000 & 8000 & 7000 Series Desktop Processors

Chipset: AMD X870E

Bluetooth: 5.4

Graphics: 1 x HDMI™ port; 2 x USB4® (40Gbps) ports support USB Type-C® display outputs

Expansion Slots: AMD Ryzen™ 9000 & 7000 Series Desktop Processors; 1 x PCIe 5.0 x16 slot (supports x16 mode); AMD Ryzen™ 8000 Series Desktop Processors; 1 x PCIe 4.0 x16 slot (supports x8/x4 mode); AMD X870E Chipset; 1 x PCIe 4.0 x16 slot

(supports x4 mode)

Storage: Total supports 5 x M.2 slots and 4 x SATA 6Gb/s ports*;AMD Ryzen™ 9000 & 7000 Series Desktop

Processors;M.2_1 slot (Key M), type 2242/2260/2280 (supports PCIe 5.0 x4 mode);M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe 5.0 x4 mode);M.2_3 slot (Key M), type 2242/2260/2280/22110 (supports PCIe 5.0 x4 mode);AMD Ryzen™ 8000 Series Desktop Processors;M.2_1 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode);M.2_2 slot (Key M), type 2242/2260/2280 (Not supports)**;M.2_3 slot (Key M), type 2242/2260/2280/22110 (Not supports);AMD X870E Chipset;M.2_4 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode);M.2_5 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode);4 x SATA 6Gb/s ports

I/O: 2 x USB4® (40Gbps) ports (2 x USB Type-C®);1 x USB 20Gbps port (1 x USB Type-C® with up to 30W PD

Fast-charge);10 x USB 10Gbps ports (9 x Type-A + 1 x USB Type-C®);1 x HDMI™ port;1 x Wi-Fi Module;1 x Realtek 5Gb Ethernet;2 x Gold-plated audio jacks ;1 x Optical S/PDIF out port;1 x BIOS FlashBack™ button ;1 x Clear CMOS button

Connectors: Fan and Cooling related ;1 x 4-pin CPU Fan header;1 x 4-pin CPU OPT Fan header;1 x 4-pin AIO Pump header;5 x 4-pin Chassis Fan headers;Power related ;1 x 24-pin Main Power connector;2 x 8-pin +12V CPU Power connectors;Storage related ;5 x M.2 slots (Key M) ;4 x SATA 6Gb/s ports;USB 1 x USB 20Gbps connector (supports USB Type-C®);2 x USB 5Gbps headers support additional 4 USB 5Gbps ports;3 x USB 2.0 headers support additional 6 USB 2.0 ports ;Miscellaneous;3 x Addressable Gen 2 headers;1 x CPU Over Voltage jumper;1 x FlexKey button ;1 x Front Panel Audio header (F_AUDIO);1 x Start button;1 x 10-1 pin System Panel header;1 x Thermal Sensor header

Audio: ROG SupremeFX 7.1 Surround Sound High Definition Audio CODEC ALC4080*;- Impedance sense for front and rear headphone outputs;- Supports: Jack-detection, Multi-streaming, Front Panel MIC Jack-retasking;- High quality 120 dB SNR stereo playback output and 110 dB SNR recording input;- Supports up to 32-Bit/384 kHz playback;Audio Features ; - Audio Shielding-Savitech SV3H712 AMP;- Gold-plated audio jacks;- Rear optical S/PDIF out port ; - Premium audio capacitors;- Audio cover;* The LINE OUT port on the rear panel does not support spatial audio. If you wish to use spatial audio, make sure to connect your audio output device to the audio jack on the front panel of your chassis or use a USB interface audio device.

LAN: 1 x Realtek 5Gb Ethernet;ASUS LANGuard

BIOS: 256 Mb Flash ROM, UEFI AMI BIOS

Form Factor: ATX Form Factor;30.5 cm x 24.4 cm



OS: Windows® 11 64-bit

Цена : 1291.63 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 21 юли, 2025

July 23, 2025, 2:06 PM