

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

ASUS PRIME H610M-A D4-CSM

Модел : ASUS PRIME H610M-A D4-CSM

ASUS PRIME H610M-A D4-CSM

USB: Rear USB (Total 6 ports); 2 x USB 3.2 Gen 2 ports (2 x Type-A); 4 x USB 2.0 ports (4 x Type-A); Front USB (Total 5 ports); 1 x USB 3.2 Gen 1 header supports additional 2 USB 3.2 Gen 1 ports; 2 x USB 2.0 headers support additional 3 USB 2.0 ports

Manufacturer: ASUS

Wireless: V-M.2 slot only (Key E, CNVi & PCIe)

Memory type: 2 x DIMM, Max. 64GB, DDR4 3200/ 3000/ 2933/ 2800/ 2666/ 2400/ 2133 Non-ECC, Un-buffered Memory; Dual Channel Memory Architecture; Supports Intel® Extreme Memory Profile (XMP)

Features: ASUS 5X PROTECTION III; - DIGI+ VRM; - LANGuard; - Overvoltage Protection; - SafeSlot Core; - Stainless-Steel Back I/O; ASUS Q-Design; - Q-DIMM; - Q-Slot; ASUS Thermal Solution; - VRM heatsink design; AURA Sync; - AURA RGB headers; - Addressable Gen 2 headers

CPU's supported: Intel® Socket LGA1700 for Intel® Core™ 14th & 13th Gen Processors, Intel® Core™ 12th Gen, Pentium® Gold and Celeron® Processors; Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0

Chipset: Intel® H610 Chipset

Graphics: 1 x DisplayPort; 1 x D-Sub port; 1 x HDMI® port

Expansion Slots: Intel® Core™ Processors (14th & 13th & 12th Gen); 1 x PCIe 4.0 x16 slot; Intel® H610 Chipset; 1 x PCIe 3.0 x1 slot

Storage: Total supports 2 x M.2 slots and 4 x SATA 6Gb/s ports; Intel® H610 Chipset; M.2_1 slot (Key M), type 2242/2260/2280 (supports PCIe 3.0 x4 mode); M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe 3.0 x2 mode); 4 x SATA 6Gb/s ports

I/O: 2 x USB 3.2 Gen 2 ports (2 x Type-A); 4 x USB 2.0 ports (4 x Type-A); 1 x DisplayPort; 1 x HDMI® port; 1 x D-Sub port; 1 x V-M.2 slot (Key E); 1 x Intel® 1Gb Ethernet port; 3 x Audio jacks; 1 x PS/2 Keyboard (purple) port; 1 x PS/2 Mouse (green) port

Connectors: Fan and Cooling related; 1 x 4-pin CPU Fan header; 2 x 4-pin Chassis Fan headers; Power related; 1 x 24-pin Main Power connector; 1 x 8-pin +12V Power connector; Storage related; 2 x M.2 slots (Key M); 4 x SATA 6Gb/s ports; USB; 1 x USB 3.2 Gen 1 header supports additional 2 USB 3.2 Gen 1 ports; 2 x USB 2.0 headers support additional 3 USB 2.0 ports; Miscellaneous; 3 x Addressable Gen 2 headers; 2 x AURA RGB headers; 1 x Clear

CMOS header;1 x Front Panel Audio header (AAFP);1 x COM Port header;1 x S/PDIF Out header;1 x Speaker header;1 x SPI TPM header (14-1pin);1 x 10-1 pin System Panel header
Audio: Realtek 7.1 Surround Sound High Definition Audio CODEC*;- Supports: Jack-detection, Multi-streaming, Front Panel Jack-retasking;- Supports up to 24-Bit/192 kHz playback;Audio Features;- Audio Shielding;- Premium audio capacitors;- Dedicated audio PCB layers;* A chassis with an HD audio module in the front panel is required to support 7.1 Surround Sound audio output.
LAN: 1 x Intel® 1Gb Ethernet
BIOS: 128 Mb Flash ROM, UEFI AMI BIOS
Form Factor: mATX Form Factor;24.4 cm x 21.1 cm
OS: Windows® 11 64-bit, Windows® 10 64-bit

Цена : 169.09 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 21 юли, 2025