

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

ASUS PRIME B760M-R D4

Модел : ASUS PRIME B760M-R D4

ASUS PRIME B760M-R D4

USB: Rear USB (Total 8 ports); 4 x USB 5Gbps ports (4 x Type-A); 4 x USB 2.0 ports (4 x Type-A)*; Front USB (Total 6 ports); 1 x USB 5Gbps header supports 2 additional USB 5Gbps ports; 2 x USB 2.0 headers support 4 additional USB 2.0 ports; * USB_E1 port, USB_E2 port, USB_E3 port and USB_E4 port share the bandwidth
Manufacturer: ASUS

Memory type: 2 x DIMM slots, Max. 64GB, DDR4; 5333(OC)/ 5066(OC)/ 5000(OC)/ 4800(OC)/ 4600(OC)/ 4400(OC)/ 4266(OC)/ 4000(OC)/ 3733(OC)/ 3600(OC)/ 3466(OC)/ 3400(OC)/ 3333(OC)/ 3200/ 3000/ 2933/ 2800/ 2666/ 2400/ 2133 Non-ECC, Un-buffered Memory; Dual channel memory architecture; Supports Intel® Extreme Memory Profile (XMP) memory module

Features: ASUS 5X PROTECTION III; - DIGI+ VRM; - LANGuard; - Overvoltage protection; - SafeSlot Core; - Stainless-steel back I/O; ASUS Q-Design- Q-DIMM; - Q-LED Core; - Q-Slot; ASUS EZ DIY; - ProCool; ASUS Thermal Solution; - VRM heatsink design; Aura Sync; - Addressable Gen 2 headers

CPU's supported: Intel® Socket LGA1700 for Intel® Core™ 14th & 13th Gen Processors, Intel® Core™ 12th Gen, Pentium® Gold and Celeron® Processors; Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0

Chipset: Intel® B760 Chipset

Graphics: 1 x HDMI™ port

Expansion Slots: Intel® Core™ Processors (14th & 13th & 12th Gen); 1 x PCIe 4.0 x16 slot; Intel® B760 Chipset; 2 x PCIe 4.0 x1 slots

Storage: Total supports 2 x M.2 slots and 4 x SATA 6Gb/s ports*; Intel® Core™ Processors (14th & 13th & 12th Gen); M.2_1 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode); Intel® B760 Chipset; M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode); 4 x SATA 6Gb/s ports; * Intel® Rapid Storage Technology supports SATA RAID 0/1/5/10

I/O: 4 x USB 5Gbps ports (4 x Type-A); 4 x USB 2.0 ports (4 x Type-A); 1 x HDMI™ port; 1 x Realtek 2.5Gb Ethernet port; 3 x Audio jacks

Connectors: Fan and Cooling Related; 1 x 4-pin CPU Fan header; 2 x 4-pin Chassis Fan headers; Power Related; 1 x 24-pin Main Power connector; 1 x 8-pin +12V Power connector; Storage Related; 2 x M.2 slots (Key M); 4 x SATA 6Gb/s ports; USB1 x USB 5Gbps header supports 2 additional USB 5Gbps ports; 2 x USB 2.0

headers support 4 additional USB 2.0 portMiscellaneous;3 x Addressable Gen 2 headers;1 x Clear CMOS header;1 x COM Port header1 x Front panel audio header (F_AUDIO);1 x S/PDIF Out header;1 x Speaker header;1 x SPI TPM header (14-1pin);1 x 10-1 pin System Panel header

Audio: Realtek 7.1 Surround Sound High Definition Audio CODEC*;- Supports: Jack-detection, Multi-streaming, Front Panel Jack-retasking;- Supports up to 24-Bit/192 kHz playback;Audio Features;- Audio Shielding;- Premium audio capacitors;- Dedicated audio PCB layers;* A chassis with an HD audio module in the front panel is required to support 7.1 Surround Sound audio output

LAN: 1 x Realtek 2.5Gb Ethernet

BIOS: 128 Mb Flash ROM, UEFI AMI BIOS

Form Factor: micro-ATX Form Factor;24.4cm x 21.1cm

OS: Windows® 11, Windows® 10 64-bit

Цена : 255.28 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 21 юли, 2025