

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

ASUS PRIME Z790-P WIFI

Модел : ASUS PRIME Z790-P WIFI

ASUS PRIME Z790-P WIFI

USB: Rear USB (Total 8 ports); 1 x USB 3.2 Gen 2x2 port (1 x USB Type-C®); 1 x USB 3.2 Gen 2 port (1 x Type-A); 2 x USB 3.2 Gen 1 ports (2 x Type-A); 4 x USB 2.0 ports (4 x Type-A); Front USB (Total 9 ports); 1 x USB 3.2 Gen 2 connector (supports USB Type-C®); 2 x USB 3.2 Gen 1 headers support 4 additional USB 3.2 Gen 1 ports; 2 x USB 2.0 headers support 4 additional USB 2.0 ports

Manufacturer: ASUS

Wireless: Wi-Fi 6; 2x2 Wi-Fi 6 (802.11 a/b/g/n/ac/ax); Supports 2.4/5GHz frequency band; Bluetooth® v5.2

Memory type: 4 x DIMM, Max. 192GB, DDR5 7200+(OC)/ 7000(OC)/ 6800(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/ 6000(OC)/ 5800(OC)/ 5600/ 5400/ 5200/ 5000/ 4800 Non-ECC, Un-buffered Memory; Dual Channel Memory Architecture; Supports Intel® Extreme Memory Profile (XMP); OptiMem II

Features: ASUS 5X PROTECTION III; - DIGI+ VRM (- Digital power design with DrMOS); - LANGuard; - Overvoltage Protection; - SafeSlot Core+; - Stainless-Steel Back I/O; ASUS Q-Design; - Q-DIMM; - Q-Slot; - Q-LED CoreASUS Thermal Solution; - Flexible M.2 heatsink; - VRM heatsink design; ASUS EZ DIY; - ProCool; Aura Sync; - Aura RGB headers; - Addressable Gen 2 headers
CPU's supported: Intel® Socket LGA1700 for Intel® Core™ 14th & 13th Gen Processors, Intel® Core™ 12th Gen, Pentium® Gold and Celeron® Processors; Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0

Chipset: Intel® Z790 Chipset

Bluetooth: 5.2

Graphics: 1 x DisplayPort; 1 x HDMI® port

Expansion Slots: Intel® Core™ Processors (14th & 13th & 12th Gen); 1 x PCIe 5.0 x16 slot Intel® Z790 Chipset; 3 x PCIe 4.0 x16 slots (support x4 mode); 1 x PCIe 3.0 x1 slot

Storage: Total supports 3 x M.2 slots and 4 x SATA 6Gb/s ports*; Intel® Core™ Processors (14th & 13th & 12th Gen)*; M.2_1 slot (Key M), type 2242/ 2260/ 2280/ 22110 (supports PCIe 4.0 x4 mode); Intel® Z790 Chipset; M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode); M.2_3 slot (Key M), type 2242/2260/2280/22110 (supports PCIe 4.0 x4 & SATA modes); 4 x SATA 6Gb/s ports; * Intel® Rapid Storage Technology supports PCIe RAID 0/1/5/10, SATA RAID 0/1/5/10

I/O: 1 x USB 3.2 Gen 2x2 port (1 x USB Type-C®); 1 x USB 3.2 Gen 2 port (1 x Type-A); 2 x USB 3.2 Gen 1 ports (2 x Type-A); 4 x USB 2.0 ports (4 x Type-A); 1 x DisplayPort; 1 x HDMI® port; 1 x

Wi-Fi Module; 1 x Realtek 2.5Gb Ethernet port; 3 x Audio jacks; 1 x PS/2 Keyboard/Mouse combo port

Connectors: Fan and Cooling related; 1 x 4-pin CPU Fan header; 1 x 4-pin CPU OPT Fan header; 1 x 4-pin AIO Pump header; 3 x 4-pin Chassis Fan headers; Power related; 1 x 24-pin Main Power connector; 1 x 8-pin +12V Power connector; 1 x 4-pin +12V Power connector; Storage related; 3 x M.2 slots (Key M); 4 x SATA 6Gb/s ports; USB; 1 x USB 3.2 Gen 2 connector (supports USB Type-C®); 2 x USB 3.2 Gen 1 headers support 4 additional USB 3.2 Gen 1 ports; 2 x USB 2.0 headers support 4 additional USB 2.0 ports; Miscellaneous; 3 x Addressable Gen 2 headers; 2 x Aura RGB headers; 1 x Clear CMOS header; 1 x COM Port header; 1 x Front Panel Audio header (AAFP); 1 x S/PDIF Out header; 1 x SPI TPM header (14-1pin); 1 x 20-5pin System Panel header; 1 x Thunderbolt™ (USB4®) Header

Audio: Realtek 7.1 Surround Sound High Definition Audio CODEC*; Supports: Jack-detection, Multi-streaming, Front Panel Jack-retasking; Supports up to 24-Bit/192 kHz playback; Audio Features; Audio Shielding; Premium audio capacitors; Dedicated audio PCB layers; * A chassis with an HD audio module in the front panel is required to support 7.1 Surround Sound audio output

LAN: 1 x Realtek 2.5Gb Ethernet

BIOS: 192 (128+64) Mb Flash ROM, UEFI AMI BIOS

Form Factor: ATX Form Factor; 30.5 cm x 23.4 cm

OS: Windows® 11, Windows® 10 64-bit

Цена : 560.72 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 21 юли, 2025