

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

ASUS PRIME B860M-K

Модел : ASUS PRIME B860M-K

ASUS PRIME B860M-K

USB: Rear USB (Total 6 ports); 1 x USB 10Gbps port (1 x Type-A); 2 x USB 5Gbps ports (2 x Type-A); 3 x USB 2.0 ports (3 x Type-A); Front USB (Total 7 ports); 1 x USB 5Gbps connector (supports USB Type-C®); 1 x USB 5Gbps header supports 2 additional USB 5Gbps ports; 2 x USB 2.0 headers support 4 additional USB 2.0 ports

Manufacturer: ASUS

Memory type: 2 x DIMM slots, max. 128GB, DDR5; Supports up to 8800+MT/s (OC), Non-ECC, Un-buffered, Clocked Unbuffered DIMM (CUDIMM); Dual channel memory architecture; DIMM Fit; Supports Intel® Extreme Memory Profile (XMP) memory module; ASUS Enhanced Memory Profile III (AEMP III)

Features: ASUS 5X PROTECTION III; - DIGI+VRM; - LANGuard; - Overvoltage protection; - SafeSlot Core+; - Stainless-steel back I/O; ASUS Q-Design; - Q-Dashboard; - Q-DIMM; - Q-LED Core; - Q-Slot; ASUS Thermal Solution; - VRM heatsink design; ASUS EZ DIY; - ProCool; Aura Sync- Aura RGB header; - Addressable Gen2 headers

CPU's supported: Supports Intel® Core™ Ultra Processors (Series 2), LGA1851; Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0

Chipset: Intel® B860 Chipset

Graphics: 1 x DisplayPort; 1 x HDMI™ port

Expansion Slots: Intel® Core™ Ultra Processors (Series 2); 1 x PCIe 4.0 x16 slot; Intel® B860 Chipset; 2 x PCIe 4.0 x1 slots

Storage: Total supports 2 x M.2 slots and 4 x SATA 6Gb/s ports*; Intel® Core™ Ultra Processors (Series 2) * M.2_1 slot (Key M), type 2242/2260/2280 (supports PCIe 5.0 x4 mode); Intel® B860 Chipset; M.2_2 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 mode) 4 x SATA 6Gb/s ports; * Intel® Rapid Storage Technology supports SATA RAID 0/1/5/10

I/O: 1 x USB 10Gbps port (1 x Type-A); 2 x USB 5Gbps ports (2 x Type-A); 3 x USB 2.0 ports (3 x Type-A); 1 x DisplayPort; 1 x HDMI™ port; 1 x Realtek 2.5Gb Ethernet port; 3 x Audio jacks; 1 x PS/2 Keyboard/Mouse combo port

Connectors: Fan and Cooling Related; 1 x 4-pin CPU Fan header; 2 x 4-pin Chassis Fan headers; Power Related; 1 x 24-pin Main Power connector; 1 x 8-pin +12V CPU Power connector; Storage Related; 2 x M.2 slots (Key M); 4 x SATA 6Gb/s ports; USB; 1 x USB 5Gbps connector (supports USB Type-C®); 1 x USB 5Gbps header supports 2 additional USB 5Gbps ports; 2 x USB 2.0 headers

support 4 additional USB 2.0 ports; Miscellaneous; 2 x Addressable Gen2 headers; 1 x Aura RGB header; 1 x Clear CMOS header; 1 x COM Port header; 1 x Front Panel Audio header (F_AUDIO); 1 x S/PDIF Out header; 1 x SPI TPM header (14-1 pin); 1 x 10-1 pin Front Panel System header

Audio: Realtek 7.1 Surround Sound High Definition Audio CODEC*; Supports: Jack-detection, Multi-streaming, Front Panel Jack-retasking; Supports up to 24-Bit/192 kHz playback; Audio Features; Audio Shielding; Premium audio capacitors; Dedicated audio PCB layers; * A chassis with an HD audio module in the front panel is required to support 7.1 Surround Sound audio output

LAN: 1 x Realtek 2.5Gb Ethernet; ASUS LANGuard

BIOS: 256(128+128) Mb Flash ROM, UEFI AMI BIOS

Form Factor: micro-ATX Form Factor; 24.4cm x 22.2cm

OS: Windows 11(22H2 & later), Windows 10 64-bit(21H2 & later)

Цена : 360.00 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 21 юли, 2025