

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

ASUS ROG STRIX Z890-E GAM WIFI

Модел : ASUS ROG STRIX Z890-E GAM WIFI

ASUS ROG STRIX Z890-E GAM WIFI

USB: Rear USB (Total 14 ports); 2 x Thunderbolt™ 4 (2 x USB Type-C®); 9 x USB 10Gbps ports (7 x Type-A + 1 x USB Type-C®* + 1 x USB Type-C® with up to 30W PD Fast-charge)**; 3 x USB 5Gbps ports (3 x Type-A); Front USB (Total 11 ports); 1 x USB 20Gbps connector (supports USB Type-C®); 2 x USB 5Gbps headers support additional 4 USB 5Gbps ports; 3 x USB 2.0 headers support additional 6 USB 2.0 ports

Manufacturer: ASUS

Wireless: Wi-Fi 7; 2x2 Wi-Fi 7 (802.11be); Supports 2.4/5/6GHz frequency band; Support Wi-Fi 7 320MHz bandwidth, up to 5.8Gbps transfer rate; Bluetooth® v5.4

Memory type: 4 x DIMM slots, max. 256GB, DDR5; Support up to 9200+MT/s (OC), Non-ECC, Clocked Unbuffered DIMM (CUDIMM); Dual Channel Memory Architecture; Supports Intel® Extreme Memory Profile (XMP) memory module; Supports DIMM Flex; NitroPath DRAM Technology ; DIMM Fit; ASUS Enhanced Memory Profile III (AEMP III)

Features: Extreme Engine Digi+; - 5K Black Metallic Capacitors; ASUS Q-Design ; - M.2 Q-Latch; - M.2 Q-Release; - M.2 Q-Slide; - PCIe Slot Q-Release Slim (with PCIe SafeSlot); - Q-Antenna; - Q-Code; - Q-Dashboard; - Q-LED (CPU [red], DRAM [yellow], VGA [white], Boot Device [yellow green]); - Q-Slot; ASUS Thermal Solution; - M.2 heatsinks; - M.2 heatsink backplate; - VRM heatsink design; ASUS EZ DIY; - BIOS FlashBack™ button; - BIOS FlashBack™ LED; - Clear CMOS button; - ProCool II; - Pre-mounted I/O shield; - SafeSlot; - SafeDIMM; Aura Sync; - Addressable Gen2 headers

CPU's supported: Intel® Socket LGA1851 for Intel® Core™ Ultra Processors (Series 2); Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0

Chipset: Intel® Z890 Chipset

Bluetooth: 5.4

Graphics: 1 x DisplayPort; 1 x HDMI® port; 2 x Intel® Thunderbolt™ 4 support DisplayPort and Thunderbolt™ video outputs

Expansion Slots: Intel® Core™ Ultra Processors (Series 2); 1 x PCIe 5.0 x16 slot (supports x16 or x8/x4/x4 modes); Intel® Z890 Chipset; 1 x PCIe 4.0 x16 slot (supports x4 mode)

Storage: Total supports 7 x M.2 slots and 4 x SATA 6Gb/s ports; Intel® Core™ Ultra Processors (Series 2); M.2_1 slot (Key M), type 2242/2260/2280/22110 (supports PCIe 5.0 x4 mode); M.2_2

slot (Key M), type 2280 (supports PCIe 4.0 x4 mode); M.2_3 slot (Key M), type 2242/2260/2280 (supports PCIe 5.0 x4 mode); M.2_4 slot (Key M), type 2242/2260/2280 (supports PCIe 5.0 x4 mode); Intel® Z890 Chipset; M.2_5 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode); M.2_6 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode); M.2_7 slot (Key M), type 2242/2260/2280 (supports PCIe 4.0 x4 & SATA modes); 4 x SATA 6Gb/s ports

I/O: 2 x Thunderbolt™ 4 (2 x USB Type-C®); 9 x USB 10Gbps ports (7 x Type-A + 1 x USB Type-C® + 1 x USB Type-C® with up to 30W PD Fast-charge); 3 x USB 5Gbps ports (3 x Type-A); 1 x DisplayPort; 1 x HDMI® port; 1 x Wi-Fi Module; 1 x Realtek 5Gb Ethernet; 2 x Gold-plated audio jacks; 1 x Optical S/PDIF out port; 1 x BIOS FlashBack™ button; 1 x Clear CMOS button
Connectors: Fan and Cooling related; 1 x 4-pin CPU Fan header; 1 x 4-pin CPU OPT Fan header; 1 x 4-pin AIO Pump header; 5 x 4-pin Chassis Fan headers; Power related; 1 x 24-pin Main Power connector; 2 x 8-pin +12V CPU Power connectors; Storage related; 7 x M.2 slots (Key M); 4 x SATA 6Gb/s ports; USB; 1 x USB 20Gbps connector (supports USB Type-C®); 2 x USB 5Gbps headers support additional 4 USB 5Gbps ports; 3 x USB 2.0 headers support additional 6 USB 2.0 ports; Miscellaneous; 3 x Addressable Gen2 headers; 1 x Chassis Intrusion header; 1 x CPU Over Voltage jumper; 1 x FlexKey button; 1 x Front Panel Audio header (F_AUDIO); 1 x Start button; 1 x 10-1 pin System Panel header; 1 x Alteration PCIe mode switch; 1 x Thermal Sensor header; 1 x Thunderbolt™ (USB4®) header

Audio: ROG SupremeFX 7.1 Surround Sound High Definition Audio CODEC ALC4080*; Impedance sense for front and rear headphone outputs; Supports: Jack-detection, Multi-streaming, Front Panel MIC Jack-retasking; High quality 120 dB SNR stereo playback output and 110 dB SNR recording input; Supports up to 32-Bit/384 kHz playback on front panel; Audio Features; Audio Shielding; Savitech SV3H712 AMP; Gold-plated audio jacks; Rear optical S/PDIF out port; Premium audio capacitors; Audio cover

LAN: 1 x Realtek 5Gb Ethernet; ASUS LANGuard

BIOS: 256 Mb Flash ROM, UEFI AMI BIOS

Form Factor: ATX Form Factor; 30.5 cm x 24.4 cm

OS: Windows® 11 (22H2 & later)

Цена : 1208.72 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 21 юли, 2025