

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

GB B650 UD AX / AMP

Модел : GB B650 UD AX / AM5

GB B650 UD AX / AMP

USB: CPU:- 2 x USB 3.2 Gen 2 Type-A ports (red) on the back panel;- 1 x USB Type-C® port on the back panel, with USB 3.2 Gen 1 support;CPU+USB 2.0 Hub:- 4 x USB 2.0/1.1 ports on the back panel;Chipset:- 2 x USB 3.2 Gen 1 ports available through the internal USB header;- 1 x USB Type-C® port with USB 3.2 Gen 1 support, available through the internal USB header;- 4 x USB 2.0/1.1 ports (2 ports on the back panel, 2 ports available through the internal USB header);Chipset+USB 2.0 Hub:- 4 x USB 2.0/1.1 ports available through the internal USB headers

Manufacturer: GIGABYTE

Wireless: Realtek® RTL8851 WIFI 6 module;- WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands;- Support for 11ax wireless standard

Memory type: Support for DDR5 8000(OC)/ 7800(OC)/ 7600(OC)/ 7200(OC)/ 7000(OC)/ 6800(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/ 6000(OC)/ 5600(OC)/ 5200/ 4800 MT/s memory modules;4 x DDR5 DIMM sockets supporting up to 256 GB (64 GB single DIMM capacity) of system memory;Dual channel memory

architecture;Support for non-ECC Un-buffered DIMM

1Rx8/2Rx8/1Rx16 memory modules;Support for AMD EXtended Profiles for Overclocking (AMD EXPO™) and Extreme Memory Profile (XMP) memory modules

Features: Support for GIGABYTE Control Center (GCC);* Available applications in GCC may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.;Support for Q-Flash;Support for Q-Flash Plus

CPU's supported: AMD Socket AM5, support for:;AMD Ryzen™ 7000 / Ryzen™ 8000 / Ryzen™ 9000 Series Processors

Chipset: AMD B650 Chipset

Graphics: Integrated Graphics Processor:- 1 x DisplayPort, supporting a maximum resolution of 3840x2160@144 Hz;* Support for DisplayPort 1.4 version.- 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz;* Support for HDMI 2.1 version and HDCP 2.3.;** Support for native HDMI 2.1 TMDS compatible ports.

Expansion Slots: 1 x PCI Express x16 slot (PCIEX16), integrated in the CPU;- AMD Ryzen™ 7000 Series Processors/ Ryzen™ 9000 Series Processors support PCIe 4.0 x16 mode;- AMD Ryzen™ 8000 Series-Phoenix 1 Processors support PCIe 4.0 x8 mode;- AMD Ryzen™ 8000 Series-Phoenix 2 Processors support PCIe 4.0

x4 mode;* The PCIe16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIe16 slot.;2 x PCI Express x16 slots (PCIEX1_1/PCIEX1_2), integrated in the CPU, supporting PCIe 3.0 and running at x1;* The PCIe1_1 and PCIe1_2 slots become unavailable when an AMD Ryzen™ 8000 Series-Phoenix 2 processor is used.;1 x PCI Express x16 slot (PCIEX1_3), integrated in the Chipset, supporting PCIe 3.0 and running at x1

Storage: 1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type 25110/ 22110/ 2580/ 2280 SSDs;:- AMD Ryzen™ 7000 Series Processors/ Ryzen™ 9000 Series Processors support PCIe 5.0 x4/x2 SSDs;:- AMD Ryzen™ 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDs;:- AMD Ryzen™ 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4/x2 SSDs;1 x M.2 connector (M2P_CPU), integrated in the CPU, supporting Socket 3, M key, type 22110/2280 SSDs;:- AMD Ryzen™ 7000 Series Processors/ Ryzen™ 9000 Series Processors support PCIe 4.0 x2 SSDs;:- AMD Ryzen™ 8000 Series-Phoenix 1 Processors support PCIe 4.0 x2 SSDs;:- AMD Ryzen™ 8000 Series-Phoenix 2 Processors support PCIe 4.0 x2 SSDs;1 x M.2 connector (M2C_SB), integrated in the Chipset, supporting Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support);4 x SATA 6Gb/s connectors;RAID 0, RAID 1, and RAID 10 support for NVMe SSD storage devices;RAID 0, RAID 1, and RAID 10 support for SATA storage devices

I/O: ITE® I/O Controller Chip

Connectors: Internal I/O Connectors;1 x 24-pin ATX main power connector;1 x 8-pin ATX 12V power connector;1 x CPU fan header;1 x CPU fan/water cooling pump header;2 x system fan headers;1 x system fan/water cooling pump header;3 x addressable RGB Gen2 LED strip headers;1 x RGB LED strip header;3 x M.2 Socket 3 connectors;4 x SATA 6Gb/s connectors;1 x front panel header;1 x front panel audio header;1 x USB Type-C® header, with USB 3.2 Gen 1 support;1 x USB 3.2 Gen 1 header;3 x USB 2.0/1.1 headers;1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only);1 x Q-Flash Plus button;1 x serial port header;1 x Clear CMOS jumper;Back Panel Connectors;1 x DisplayPort;1 x HDMI port;1 x PS/2 keyboard/mouse port;2 x SMA antenna connectors (2T2R);1 x USB Type-C® port, with USB 3.2 Gen 1 support;2 x USB 3.2 Gen 2 Type-A ports (red);6 x USB 2.0/1.1 ports;1 x RJ-45 port;3 x audio jacks

Audio: Realtek® Audio CODEC;ALC897;High Definition Audio;2/4/5.1/7.1-channel

LAN: Realtek® RTL8111H GbE LAN chip (1 Gbps/100 Mbps/10 Mbps)

BIOS: 1 x 256 Mbit flash;Use of licensed AMI UEFI BIOS;PnP 1.0a,



DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Form Factor: ATX Form Factor; 30.5cm x 24.4cm

OS: Support for Windows 11 64-bit; Support for Windows 10 64-bit

Цена : 307.63 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 25 юли, 2025