

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

GB B650 A ELITE AX V2 / AMP

Модел : GB B650 A ELITE AX V2 / AM5

GB B650 A ELITE AX V2 / AMP

USB: CPU:- 1 x USB Type-C® port on the back panel, with USB 3.2 Gen 2 support;- 2 x USB 3.2 Gen 2 Type-A ports (red) on the back panel;CPU + USB 2.0 Hub:- 4 x USB 2.0/1.1 ports on the back panel;Chipset:- 1 x USB Type-C® port with USB 3.2 Gen 2x2 support, available through the internal USB header;- 3 x USB 3.2 Gen 1 ports (1 port on the back panel, 2 ports available through the internal USB header);- 4 x USB 2.0/1.1 ports available through the internal USB headers;Chipset+USB 3.2 Gen 1 Hub:- 4 x USB 3.2 Gen 1 ports on the back panel

Manufacturer: GIGABYTE

Wireless: Realtek® Wi-Fi 6E RTL8852CE (PCB rev. 1.0);- WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands;- BLUETOOTH 5.3;- Support for 11ax 160MHz wireless;Intel® Wi-Fi 6E AX210 (PCB rev. 1.1)

Memory type: Support for DDR5 8000(OC)/ 7800(OC)/ 7600(OC)/ 7200(OC)/ 7000(OC)/ 6800(OC)/ 6666(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/ 6000(OC)/ 5600(OC)/ 5200/ 4800/ 4400 MT/s memory modules;4 x DDR5 DIMM sockets supporting up to 256 GB (64 GB single DIMM capacity) of system memory;Dual channel memory architecture;Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules;Support for AMD EXTended Profiles for Overclocking (AMD EXPO™) and Extreme Memory Profile (XMP) memory module

Features: Support for GIGABYTE Control Center (GCC);* Available applications in GCC may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.;Support for Q-Flash;Support for Q-Flash Plus

CPU's supported: AMD Socket AM5, support for:;AMD Ryzen™ 7000 / Ryzen™ 8000 / Ryzen™ 9000 Series Processors

Chipset: AMD B650

Bluetooth: 5.3

Graphics: Integrated Graphics Processor with AMD Radeon™ Graphics support:- 1 x DisplayPort, supporting a maximum resolution of 3840x2160@144 Hz;* Support for DisplayPort 1.4 version and HDR.;- 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz;* Support for HDMI 2.1 version and HDCP 2.3.;** Support for native HDMI 2.1 TMDS compatible ports.

Expansion Slots: 1 x PCI Express x16 slot (PCIEX16), integrated in the CPU;- AMD Ryzen™ 7000 Series Processors/ Ryzen™ 9000

Series Processors support PCIe 4.0 x16 mode;- AMD Ryzen™ 8000 Series-Phoenix 1 Processors support PCIe 4.0 x8 mode;- AMD Ryzen™ 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4 mode;* The PCIe x16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIe x16 slot.; Chipset:- 2 x PCI Express x16 slots, supporting PCIe 3.0 and running at x1 (PCIEX1_1/2) Storage: 1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type 25110/ 22110/ 2580/ 2280 SSDs;- AMD Ryzen™ 7000 Series Processors/ Ryzen™ 9000 Series Processors support PCIe 5.0 x4/x2 SSDs;- AMD Ryzen™ 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDs;- AMD Ryzen™ 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4/x2 SSDs; 1 x M.2 connector (M2B_CPU), integrated in the CPU, supporting Socket 3, M key, type 25110/22110/2580/2280 SSDs;- AMD Ryzen™ 7000 Series Processors/ Ryzen™ 9000 Series Processors support PCIe 4.0 x4/x2 SSDs;- AMD Ryzen™ 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDs;- AMD Ryzen™ 8000 Series-Phoenix 2 Processors support PCIe 4.0 x2 SSDs; 1 x M.2 connector (M2C_SB), integrated in the Chipset, supporting Socket 3, M key, type 25110/22110/2580/2280 PCIe 4.0 x4/x2 SSDs; 4 x SATA 6Gb/s connectors; RAID 0, RAID 1, and RAID 10 support for NVMe SSD storage devices; RAID 0, RAID 1, and RAID 10 support for SATA storage devices I/O: ITE® I/O Controller Chip Connectors: Internal I/O Connectors; 1 x 24-pin ATX main power connector; 1 x 8-pin ATX 12V power connector; 1 x 4-pin ATX 12V power connector; 1 x CPU fan header; 1 x CPU fan/water cooling pump header; 3 x system fan headers; 1 x system fan/water cooling pump header; 3 x addressable RGB Gen2 LED strip headers; 1 x RGB LED strip header; 3 x M.2 Socket 3 connectors; 4 x SATA 6Gb/s connectors; 1 x front panel header; 1 x front panel audio header; 1 x USB Type-C® header, with USB 3.2 Gen 2x2 support; 1 x USB 3.2 Gen 1 header; 2 x USB 2.0/1.1 headers; 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only); 1 x reset button; 1 x reset jumper; 1 x Clear CMOS jumper; Back Panel Connectors; 1 x Q-Flash Plus button; 2 x antenna connectors (2T2R); 1 x DisplayPort; 1 x HDMI port; 1 x USB Type-C® port, with USB 3.2 Gen 2 support; 2 x USB 3.2 Gen 2 Type-A ports (red); 5 x USB 3.2 Gen 1 ports; 4 x USB 2.0/1.1 ports; 1 x RJ-45 port; 3 x audio jacks Audio: Realtek® Audio CODEC; High Definition Audio; 2/4/5.1/7.1-channel LAN: Realtek® 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps) BIOS: 1 x 256 Mbit flash; Use of licensed AMI UEFI BIOS; PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0



Form Factor: ATX Form Factor; 30.5cm x 24.4cm

OS: Support for Windows 11 64-bit; Support for Windows 10 64-bit

Цена : 413.47 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 25 юли, 2025