

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Dell Networking N1524P, PoE+, 24x 1GbE + 4x 10GbE SFP+ fixed ports, Stacking, IO to PSU airflow, AC 210-AEVY CAMPUS Smart Value Dell EMC Networking N1524P



Модел : DNN1524P

Dell Networking N1524P, PoE+, 24x 1GbE + 4x 10GbE SFP+ fixed ports, Stacking, IO to PSU airflow, AC 210-AEVY CAMPUS Smart Value Dell EMC Networking N1524P

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): Support IEEE 802.3at PoE plus standard

Uplink портове: 4x10GE SFP

Свободни (10GB) слотове: No

Управление: Management via an intuitive and familiar CLI, embedded web server (GUI), SNMP-based management console application (including Dell OpenManage Network Manager), Telnet or serial connection.

Stackable: Yes

Fans: Redundant variable speed fans

Захранване: Integrated power supply: 600W AC; Optional external power supply MPS1000 (sold separately)

Routing: Layer 3 RIP

Памет (Flash, RAM): Flash Memory: 256 MB, RAM: 1 GB

Капацитет за маршрутизиране/превключване, Gbps: 128 Gbps

Пропускателна способност, Mpps: 128 Mpps

MAC адреси: 16000 MAC address table size

VLAN (брой, стандарти): 802.1Q VLAN Tagging, Double VLAN Tagging, GVRP; Private VLAN extensions and Private VLAN Edge support; 128 VLAN routing interfaces; 512 VLANs supported; Protocol-based VLANs; Max VLAN interfaces with ACLs applied: 24

QoS: 8 priority queues per port, DiffServ, Flow Based QoS, Port Based QoS

L2 мрежови стандарти: IEEE 802.1AB, IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1S, IEEE 802.1v, IEEE 802.1W, IEEE 802.1X, IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ac, IEEE 802.3ad, IEEE 802.3ae/at, IEEE 802.3AX, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z

L3 мрежови стандарти: Static routing and Routing Information Protocol (RIPv1, RIPv2); 128 RIP routing interfaces

IPv6 functionality: General IPv6 protocols are supported
Сигурност: AAA authorization, TACACS+ accounting and
RADIUS support for comprehensive secure access support
Размери (Ш, Д, В), mm: 440 x 387 x 43
Опция за монтаж: Rackmount
Други: RJ45 console port with RS232 signaling (RJ-45 to
female DB-9 connector cable included), USB (Type A) port
for configuration via USB flash drive

Цена : 4224.46 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Вт 10 юни, 2025