

МРЕЖОВА ТЕХНИКА > СВИЧОВЕ

HPE 1950 12XGT 4SFP+ Switch



Модел : JH295A

HPE 1950 12XGT 4SFP+ Switch

Свич, тип: Fixed Port

Общ брой портове: 16

Основни портове, тип: 12x10GBase-T

Power Over Ethernet (PoE): No

Uplink портове: 4x10GE SFP

Свободни (10GB) слотове: No

Управление: Intuitive Web browser-based management;
Secure Web-management sessions with HTTPS/SSL;
SNMPv1, v2c, and v3; Complete session logging; Dual flash
images; Port mirroring; RMON; NTP; IEEE 802.1AB Link Layer
Discovery Protocol (LLDP); CLI; Default DHCP client
Stackable: True stacking allows for redundancy while
simplifying administration

Fans: Variable-speed fans

Захранване: AC voltage: 100-240 VAC; Maximum power
rating: 75 W, HPE RPS800 Redundant Power Supply
(JD183A)

Routing: Layer 3 Lite

Памет (Flash, RAM): Flash Memory: 512 MB; RAM: 1 GB
SDRAM

Капацитет за маршрутизиране/превключване, Gbps: 320
Gbps

Пропускателна способност, Mpps: 238 Mpps

MAC адреси: 16384 MAC address table size

VLAN (брой, стандарти): Supports IEEE 802.1Q with 4,094
simultaneous VLAN IDs

QoS: Broadcast control, Rate limiting, Traffic prioritization
(Recognizes both IEEE 802.1p and DSCP prioritization
tagging. Packets are mapped to four hardware queues for
more effective throughput), Powerful QoS feature (SP, WRR
and SP+WRR queuing)

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE
802.3ab, IEEE 802.3ac, IEEE 802.3ad, IEEE 802.3ae, IEEE
802.3i, IEEE 802.3x, IEEE 802.3z, IEEE 802.3az, IEEE 802.1s,
IEEE 802.1w, IEEE 802.1D MAC Bridges, IEEE 802.1D STP,
IEEE 802.1p, IEEE 802.1Q

L3 мрежови стандарти: Static IPv4/IPv6 routing: provides
basic routing (supporting up to 512 static routes and 32
VLAN interface on aggregation model; 32 static routes and 8
VLAN interfaces on access models); allows manual routing
configuration

IPv6 functionality: IPv6 host, IPv6 routing, MLD snooping, IPv6 ACL/QoS

Сигурност: Access Control Lists (ACLs); IEEE 802.1X and RADIUS network logins; Port isolation; ARP attack protection; Automatic VLAN assignment; STP BPDU port protection; STP root guard; Automatic denial-of-service protection; Management password

Размери (Ш, Д, В), mm: 440 x 160 x 44

Опция за монтаж: Desktop/Rackmount

Други: 1 dual-personality (RJ-45 or Mini USB) console port to access limited CLI port; 1 RJ-45 out-of-band management port

Цена : 5283.94 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 04 юли, 2025