

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Aruba 2930F 24G 4SFP Swch



Модел : JL259A

Aruba 2930F 24G 4SFP Swch

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): No

Uplink портове: 4xSFP

Свободни (10GB) слотове: No

Управление: Aruba AirWave Network Management; IMC - Intelligent Management Center; Command-line interface; Web browser; Configuration menu; SNMP manager; Telnet; RMON1; FTP; Out-of-band management (serial RS-232C or micro USB)

Stackable: No

Fans: yes

Захранване: Internal

Routing: Layer 3 Advanced

Памет (Flash, RAM): Flash Memory: 4 GB eMMC; RAM: 1 GB DDR3 SDRAM

Капацитет за маршрутизиране/превключване, Gbps: 56 Gbps

Пропускателна способност, Mpps: 41.7 Mpps

MAC адреси: 32768 MAC address table size

VLAN (брой, стандарти): Supports IEEE 802.1Q (4,094 VLAN IDs) and 2K VLANs simultaneously, IEEE 802.1v protocol VLANs, Rapid Per-VLAN Spanning Tree (RPVST+), GVRP and MVRP, VxLAN, Jumbo packet support

QoS: Traffic prioritization (IEEE 802.1p) - Allows real-time traffic classification into eight priority levels mapped to eight queues; Layer 4 prioritization - Enables prioritization based on TCP/UDP port numbers; Class of Service (CoS); Rate limiting

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3x, IEEE 802.1AB, IEEE 802.1AX-2008, IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1v, IEEE 802.1X, IEEE 802.1ap

L3 мрежови стандарти: Static IP routing; 256 static and 10000 RIP routes; Routing Information Protocol (RIP) Provides RIPv1, RIPv2, and RIPv3 routing; Access OSPF - Provide OSPFv2 and OSPFv3 protocols for routing between access and the next layer on the LAN.

IPv6 functionality: IPv6 host, IPv6 routing, MLD snooping,

IPv6 ACL/QoS, Dual stack (IPv4 and IPv6)

Сигурност: IEEE 802.1X, Web/MAC-based authentication, ACLs, Source-port filtering, RADIUS/TACACS+, Secure shell, SSL, Port security, MAC address lockout, Secure FTP, STP BPDU port protection, DHCP protection, Dynamic ARP protection, STP root guard, Private VLAN

Размери (Ш, Д, В), mm: 443 x 200 x 44

Опция за монтаж: Rackmount

Други: 1 dual-personality (RJ-45 or USB micro-B) serial console port

Цена : 1769.23 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 04 юли, 2025